

Notice Inviting e-Tender

West Bengal Medical Services Corporation Limited Swasthya Sathi GN-29, Salt Lake, Sector-V Kolkata-700091

Phone No (033) 40340308/319

E mail: procurement@wbmsc.gov.in / mp@wbmsc.gov.in

Procurement of Medical Equipment for Medical College and Hospital

(Submission of Bid through online)

Bid Reference No.: WBMSCL/NIT- 215/2020 Dated- 05.11.2020

AMENDMENT-I

TECHNICAL SPECIFICATIONS

SI. 1-SPECIFICATION OF TONOMETER (SCHIOTZ)

- 1. Body
- 2. Footplate rests on the Cornea
- 3. Plunger
- 4. Weights-5.5 gm permanently fixed.

Additional weight – 7.5 gm, 10 gm, 15 gm

Safety Certification: CE ("Conformite Europeene") or US FDA Certificate or BIS

SI. 2- SPECIFICATION OF TRIAL BOX WITH TRAIL FRAME

1. TRIAL BOX (WOODEN / PLASTIC)

Trial box contains trial lenses arranged in pairs, prisms and accessories.

TRIAL LENSES

Reduced aperture lenses of 20 mm diameter mounted in the metal rim of 38mm diameter, Plano convex and Plano concave.

- 1. Spherical lenses 32 pairs present in plus and minus power. Range: + &-0.12D to + &-20.00D. Variation: 0.25 to 4.00 D in increment of 0.25 D. 4.00D to 6.00 D in increment of 0.50 D. 6.00 to 14.00 D in increment of 1.00 D. 14.00 to 20.00 D in increment of 2.00D.
- Cylindrical lenses: 19 pairs present in plus & minus form. Ranges: + &- 0.25D to &+ 6.00D. Variations: 0.25 to 3.50D in increment of 0.25D. 3.50 to 6.00 in increment of 0.50D.

PRISMS:

Power range of 0.5 D, 1-6.00D in 1D steps ,6-12.00D in 2D steps

ACCESSORIES:

- 1. Trail frame
- 2. Jackson cross cylinder
- 3. Occluder
- 4. Pin hole
- 5. Stenopic slit
- 6. Maddox rod
- 7. Red and Green Filter

TRIAL FRAME (Adult)

- Metallic/plastic adjustable trial frame
- Light weight with comfortable nose rest
- Reduced aperture to hold up to 38mm lenses for each eye. Atleast 3 compartment for spherical lenses, cylindrical lenses and occlude

Nose bridge and temple are adjustable according to patient face.

TRAIL FRAME (CHILD)

- Trail frame for children, for 3 pairs of lenses Ø38 mm
- Adjustable PD from 54-58 mm
- Fixed bridge
- Adjustable temple length
- Lightweight metal and plastic
- Comfort trail frame for children with adjustable nose rest.

SI. 3- SPECIFICATION OF DIRECT OPHTHALMOSCOPE

- 1. Apertures: 7 (Cobalt blue filter, fixation star with polar co-ordinates, large spot, small spot, slit, hemispot
- 2. All with red-free filter.
- 3. Aspherical Optical System
- 4. Optical components mounted to an aluminium chassis
- 5. Light: Xenon-Halogen
- 6. 2.5 Volt D-Cell being incorporated

Safety Certification: CE ("Conformite Europeene") or US FDA Certificate or BIS