Notice Inviting e-Tender

West Bengal Medical Services Corporation Limited Swasthya Sathi GN-29, Salt Lake, Sector-V Kolkata-700091

Phone No (033) 40340431/308 E mail: procurement@wbmsc.gov.in

PROCUREMENT OF MEDICAL EQUIPMENT FOR FIVE NEW MEDICAL COLLEGES AND HOSPITALS

(Submission of Bid through online)

Bid Reference No.: WBMSCL /NIT-40/2019 Dated -04.06.2019

The following amendment have been made in the tender document,

Amendment-I

TECHNICAL SPECIFICATIONS

Item No. - 1

Thin layer Chromatography

Purpose: To introduce the principles of absorption chromatography using the thin layer technique.

This mechanism is having moveable applicator with inbuilt thickness arrangement between 0 to 2mm (minimum div. 0.25mm) in further consists of the following components -

- a. Spreader (applicator) made of electroplated brass.
- b. Perspex base of 114x23 cm to support glass plates.
- c. Plate rack aluminium, anodised for ten 20 x 10 cm plates.
- d. Chromatography tank with lid. (20 x 20 cm)
- e. Spotting template made of perspex.
- f. TLC plates set of ten 20x10cm
- g. Glass sprayer with rubber bellow, cap. 100ml
- h. Micro-pipette
- i. Subscriber for marking lines made of stainless steel
- j. Instruction manual.
- k. Safety Standard: CE/ US FDA / BIS

Item No. - 2

Horizontal Electrophoresis Unit with Power supply (for paper, agarose)

- Complete set including base gel running unit, safety lid, at least two casting trays and combs.
- 2. Gel casting Tray: Standard form;
- 3. Combs size: 1.0 to 1.5 mm 4 wells/8 wells / 12 wells
- 4. Buffer chamber capacity: minimum 150 ml.
- 5. Buffer chamber must have safety lid
- 6. No. of platinum electrodes : positive &negative (each one)
- 7. Connecting Cord: Red and Black (each one)
- 8. Power supply:
 - > Suitable for constant voltage and constant current mode.
 - Output voltage: adjustable from 0 to 500 with an increment of 1 volt
 - > Output current: upto 800 mA with an increment of 1mA.
 - > Output power: 300W or more (450)
 - ➤ Input voltage: 230V + 10 VAC, 50Hz
- 9. Safety Standard: CE/US FDA/BIS

Item No. - 3

Vertical Slab Gel Electrophoresis Unit with Power supply

- 1. Dimensions: (| x b x h) cm : 15x15x15
- 2. Gel size (cm): 8x7
- 3. No. of samples: 4 to 8 or more
- 4. Upper buffer tank capacity (ml): 75 ml or more
- 5. Lower buffer tank Capacity (ml): 150 ml or more
- 6. No. of Combs: 4 to 8 well tooth comb
- 7. Teflon spacers: 0.5 mm Teflon spacers (2 in numbers)

1mm Teflon spacers (2 in numbers)

1.5mm Teflon Spacers (2 in numbers)

- 8. Connecting cords: Black & red
- 9. Platinum electrode : red & black : 1 each
- 10. Lid: one
- 11. Glass plate: Notched & Rectangular: 2 sets

Power Supply:

- Suitable for constant voltage and constant current mode.
- ➤ Output voltage: adjustable from 0 to 500 with an increment of 1 volt

> Output current: upto 800 mA with an increment of 1mA.

> Output power: 300W or more (450)

➤ Input voltage: 230V <u>+</u> 10 VAC, 50Hz

12. Safety Standard: CE/US FDA/BIS